



HIGH PURITY ZINC ANODES

PRODUCT CODE	NET WEIGHT OF ANODE	APPROX. WEIGHT PACKAGED	STANDARD PACKAGING
ZA-6	6 LBS	14 LBS	4" DIA X 15 1/2" WATER PERMEABLE CARDBOARD TUBE
ZA-12	12 LBS	28 LBS	4" DIA X 27 1/2" WATER PERMEABLE CARDBOARD TUBE
ZA-24	24 LBS	52 LBS	4" DIA X 51 1/2" WATER PERMEABLE CARDBOARD TUBE

CUSTOM PACKAGING UPON REQUEST

WIRE: STANDARD 10FT (3M) AWG #10 STRANDED COPPER LEAD WIRE WITH TW75 WHITE INSULATION, SILVER SOLDERED TO 1/4" DIA ELECTRO GALVANIZED STEEL CORE EXTENDING 100% OF ANODE LENGTH - CUSTOM WIRE SELECTION UPON REQUEST
 BACKFILL: GROUND HYDRATED GYPSUM - 77% +/- 1%; ANHYDROUS SODIUM SULPHATE - 8% +/- 1%; POWDERED WYOMING BENTONITE - 15% +/- 1%
 SPECIFICATION ASTM B 418 (LATEST EDITION) TYPE II

UNLESS OTHERWISE SPECIFIED:
 DIMENSIONS ARE IN MILLIMETERS
 TOLERANCES:
 FRACTIONS ± .005
 DECIMALS ± .01
 ANGLES ± 1°
 HOLE FILE SHARP CORNER 1 MM MAX
 SURFACE FINISH: 30 - 50

THIS DRAWING IS THE PRIVATE PROPERTY OF "NEK" AND CAN NOT BE USED DIRECTLY OR INDIRECTLY WITHOUT THE WRITTEN PERMISSION OF THE COMPANY. ALL LEGAL RIGHTS RESERVED.

NEK CASTINGS & INFRASTRUCTURE PRODUCTS

NAME	SIGNATURE	DATE	HEAT TREATMENT:
DRAWN: NEK		16-09-2025	
CARD:			MATERIAL:
APPROV:			ZINC
MFG:			PROJECT:
Q.A.			10
DO NOT SCALE DRAWING		WEIGHT:	

PART NAME:	REVISION:
ZINC ANODES	A
PART NUMBER:	
SHEET 1 OF 1	SCALE: 1:2
REV: AI	

REVISIONS

REV.	DATE	DESCRIPTION	EARLIER WAS	CHANGED TO
A	16-09-2025	DRAWING RELEASED	INITIAL RELEASE	INITIAL RELEASE